





Most rugged two door/four reader access controller to ensure unparalleled physical security.



HARDWARE

Doors/4 Readers bit microcontroller running at 42 MHz
Ç
28 Kbytes
MB flash
0,000 card holders
5,000 time stamped events storage capacity
Ion volatile real time clock calendar
ED indication for reader and lock activity status
O Base-T RJ45 ethernet interface (TCP/IP) with status LED indications
Veigand configurable from 26 bits to 40 bits/clock data four reader ports
ED Control, buzzer control & reader tamper switch input
Potential free changeover relays, contact rating 3A/30V DC, support both fail safe
fail secure type of lock assemblies
Optically isolated inputs for 2 door sensor, 2 exit switch & 2 general purpose digital input
nbuilt watchdog supervisor
3.8V DC / 2.5 Amp with battery charger, provision to connect 12V/7.2 AH battery
liniature circuit breaker (MCB) for over current protection
.5 Watts(excluding lock and readers)
80V AC ~ 230V AC/50 Hz
10 to 50°C
RH 5-95% non-condensing
.65 Kg.
I 230 x W 262 x D 57
(C (

FIRMWARE

Time Zone	30 user defined time zones
Access Groups	90 access groups
Day Access	Day of the week access
Week off Groups	30 week off groups
Holiday Groups	10 holiday groups, 30 holiday per group
Antipassback	Door wise antipassback
Interlocking	Interlocking facility available
Digital Inputs	Programmable general purpose digital inputs for monitoring devices and sensors
Digital Outputs	Programmable general purpose digital output for alarms

Technical specifications may be changed from time to time without any prior notice due to continuous enhancements in the product.



Mumbai (+91 22 44111222 Gurgaon

+91 124 4386354

+91 80 44111222 Hyderabad