

The faster, more efficient and more cost effective 2 Door 2 Reader Controller

KEY BENEFITS

- The Processor: Its 32 bit processor makes smart XS NG a much faster and more efficient controller in all its functions than any other controller in its category and, along with the following advantages, much more cost effective too.
- CCTV Integration with Access Events: Alarm management Software module for security audit or to verify/identify tailgating, made effective by Alert based network protocol implemented in smartXS NG.
- Door Interlocking:- smartXS NG has inbuilt configurable door interlocking facility so that if one door is open, some or all of the other three will remain closed. The Logic can be defined by the user on site through the controller Keypad.
- DIN Rail mounting option:- Available in more compact and attractive with standard DIN Rail mounting, besides the conventional panel enclosure.

Many highly prestigious organizations from many sectors such as Banking, Pharma, IT, Mega Retail, Government etc. have been using various Access Control, Time and Attendance and Security related systems of smart-i in many of their establishments all over India, for many years.



Other Benefits

Onboard TCP/IP with Online Firmware up gradation facility:- The versatile Interface makes the device technically very strong & user friendly. It gives tremendous freedom to use the infrastructure, either existing or planned. The Device has an inbuilt capability for an online up gradation of the firmware.

Reader Tamper Detection:- Device generates a temper event alert if any Reader is tampered with. Reader should have the facility of inbuilt tamper output.

Power Supply with provision for battery Backup: Gives a smooth operation under diverse power infrastructure conditions. Power supply will recharge the Battery (7AH). **(Battery is not included)**

Transactions and User Capacity:- It stores 30,000 Users/cards and 60,000 Transactions/Events.

Added Security for access to the Controller:-Configurable card/finger verification has been provided for extra security, in addition to the usual login id and password, to access the Controller device.

Enhanced Security Features:- Anti pass back, facility/establishment code, Time zone, Duress Card/finger, Dual card/Finger implementation for enhanced security. For Data downloading Security the IP address of the authorized computer/s is mapped with that of the Controller, making the downloading of the data even more secure.

Access Control Solutions



Technical Specifications

Particulars	Specifications
Model no.	SMNG220
Applications	Access Control System
	Fechnical Specification
CPU	ARM 32 Bit RISC Processor
Memory	Upto 8 MB Flash
No. of Doors	2
No. of Readers	2
Events/Transactions	60,000
No. Users	30,000
Reader Interface	Weigand (Up to 34 bit)
Input	6 inputs
mpac	(2- Door Status,
	2- Egress, 1- Fire &
	1- intrusion)
Output	4 outputs
	(2 - DOTL, 2 – Lock)
Communications Port	TCP/IP, RS485
Protocol	TCP, UDP, TCP Push, UDP Push
Door Interlocking/Man Trap	Yes
Fire Integration	Yes
Intrusion Integration	Yes
LCD	16X2 LCD Display
Keypad	
Baud Rate	4X3 Key with soft keypad 9600bps (Default)
Controller ID	• • •
	Up to 10,000 English
Language Power Supply	12 V DC/ 5A
Enclosure	
	Industry Standard Metal Enclosure
Mounting	Din Rail (Without Metal Enclosure) ,
Tomorovotuvo	Wall mount (with Metal Enclosure) 0°C to 50°C
Temperature	20% to 90%
Humidity	20% to 90%
Facility Code	Available
Time Zone / Access Levels	63 + 1 (Free Time Zone)/Unlimited
Time Zone Slots	4 slots per Day
Anti-Passback	Hard, Soft, Escort (Reader Wise)
Holiday Settings	42
	Ordering Information
Controller	SMNG220
Controller	SMNG220-DIN
(Without Metal Enclosure)	
Software	smartACCESS /
	smartCOMMANDCONTROL
Accessories	Card Reader - SC504/SPR501
	Biometrics Reader - SBSNG 150/950 Series Biometrics Reader - SBSNG 1050 Series
	Biometrics Reader - SBSNG 1050 Series or Any Standard Weigand Reader

smart-i Designs and Manufactures complete Access Control Solution including Biometric & Card Readers.

* smart-i Policy is one of constant improvement. We reserve the rights to alter specifications without any prior notice.



SMORT I ELECTRONICS SYSTEMS PVT. LTD. For more information call +91-22-6566 6555 or Email us @ enquiry@smartisystems.com www.smartisystems.com

PRESENCE: MUMBAI 🜢 DELHI 🌢 BANGALORE 🌢 KOLKATA 🌢 CHENNAI 🌢 AHMEDABAD 🌢 PUNE 🌢 HYDERABAD