


# smartXS NG *plus*

The Premium 4 Door 4 Reader Access Controller  
With 32 Bit Processor and DIN Rail Mounting



smartXS NG *plus* is a premium category 4 Door 4 Reader Access Controller, as fast and as efficient in all functions as the best in the market in this category. Better in fact, in some ways.

## KEY BENEFITS

- **The Processor:-** Its 32 bit processor makes smartXS NG *plus* a much faster and more efficient controller in all its functions at par with the other controllers in the premium category. Much more cost effective too.
- **MODBUS:-** smartXS NG *plus* has MODBUS connectivity option for integration with third party BMS (Building Management System).
- **SNMP Alerts:-** SNMP alerts for integration with IT System Administration Software for monitoring critical events ie; Door left open, unauthorized access attempt, Power Fail and Battery Low Alerts, etc.
- **Alarm management Software module:-** CCTV/IP Camera Integration with Access Events for security audit or to verify/identify tailgating, made effective by alerts based on UDP network protocol.
- **Inbuilt Web Server –** smartXS NG *plus* can be managed remotely through inbuilt web Server using any web browser.
- **4 GB SD Memory Card –** Mirror image of device configuration and data.
- **Door Interlocking -** smartXS NG *plus* has inbuilt configurable door interlocking facility for clean environment so vital in sectors such as pharma, datacenter, etc.

Many highly prestigious organizations from many sectors such as Banking, Pharma, IT, Mega Retail, Government etc. have been using various Access Control, Time and Attendance and Security related systems of smart-i in many of their establishments all over India, for many years.

## Other Benefits

**No Hidden Costs** All essentials, the Controller, Reader Interface, Power Supply, Metal Enclosures are all inbuilt, together, and do not have to be added on.

**Software & Hardware Designed in-house in India** Makes it more suitable and receptive to the Indian requirements.

**Onboard TCP/IP based Architecture with Online Firmware up gradation facility** All access decisions taken independently by each controller. The Device has an inbuilt capability for an online up gradation of the firmware.

**DIN Rail mounting option:** - Available in more compact and attractive standard DIN Rail mounting.

**Reader Tamper Detection:** - Device generates a tamper event alert if any Reader is tampered with. Reader should have the facility of inbuilt tamper output.

**Enhanced Security Features:** - Anti pass back, facility/establishment code, Time zone, Duress Card/finger, Dual card/Finger implementation for enhanced security. For Data downloading Security the IP address of the authorized computer/s is mapped with that of the Controller, making the downloading of the data even more secure.

## Access Control Solutions



**smart-i Designs and Manufactures complete Access Control Solution including Biometric & Card Readers.**

\*\*Optional

## Technical Specifications

Particulars	Specifications
<b>Model no.</b>	<b>SMNG440</b>
<b>Applications</b>	Access Control System
<b>Technical Specification</b>	
<b>CPU</b>	ARM 32 Bit RISC Processor
<b>Memory</b>	4GB SD and 8 MB Flash
<b>No. of Doors</b>	4
<b>No. of Readers</b>	4
<b>Events/Transactions</b>	Upto 4,00,000
<b>Users</b>	Upto 1,00,000
<b>Web Server</b>	Yes
<b>Door Interlocking/Man Trap</b>	Yes
<b>Global APB</b>	Yes
<b>SNMP Alerts</b>	Yes
<b>MODBUS Protocol Support</b>	Yes
<b>AC Fail/Low Battery Alert</b>	Yes
<b>Reader Interface</b>	Weigand (Up to 34 bit)
<b>Input</b>	<b>12 inputs</b> (4- Door Status, 4- Egress, 1- Fire &
<b>Output</b>	1- intrusion and 2 Extra input) <b>12 outputs</b> (4 - DOTL, 4 - Lock, 4 auxilliary output)
<b>Communications Port</b>	TCP/IP, Rs485
<b>Protocol</b>	TCP, UDP, TCP Push, UDP Push, SNMP, Modbus
<b>Fire Integration</b>	Yes
<b>Intrusion Integration</b>	Yes
<b>LCD</b>	16X2 LCD Display
<b>Keypad</b>	4X3 Key with soft keypad
<b>Baud Rate</b>	9600bps (Default)
<b>Controller ID</b>	Upto 10000
<b>Language</b>	English
<b>Power Supply</b>	12 V DC/ 5A
<b>Enclosure</b>	Industry Standard Metal Enclosure
<b>Mounting</b>	DIN Rail (without Metal Enclosure) / Wall mount (with Metal Enclosure)
<b>Access Control Features</b>	
<b>Facility Code</b>	Available
<b>Time Zone / Access Levels</b>	63 + 1 (Free Time Zone)/Unlimited
<b>Time Zone Slots</b>	4 slots per Day
<b>Anti-Passback</b>	4 slots per Day
<b>Holiday Settings</b>	4 slots per Day
<b>Ordering Information</b>	
<b>Controller</b>	42
<b>Controller (Without Metal Enclosure)</b>	SMNG440 SMNG440-DIN
<b>Software</b>	"smartENGINE" / "smartCOMMANDCONTROL"
<b>Accessories</b>	Card Reader - SC504/SPR501

\* smart-i Policy is one of constant improvement. We reserve the rights to alter specifications without any prior notice.

**smart i** ELECTRONICS SYSTEMS PVT. LTD.

For more information call +91-22-6566 6555 or

Email us @ enquiry@smartisystems.com

www.smartisystems.com